DUB-818 Safety Kwik Link 4-40



4_40_Safety_Lck__49a7570f5ca73.jpg



DUB-818 Safety Kwik Link 4-40

Rating: Not Rated Yet

Price

Price with discount \$3.41

Salesprice with discount

Sales price \$3.41

Sales price without tax \$3.41

Discount

Tax amount

Ask a question about this product

Description

These are 4-40 Safety Lock Kwik-Link Clevis' from Dubro. Used on model aircraft for connecting control rods to control surfaces.

FEATURES: Self tapping design leaves no slop on the pushrod threads. Square nylon shank for easy installation and adjustment. 10% lighter than a steel clevis. Brass plated steeped steel pin does not bind on control horns and has a large flat head for easy removal. Brass plated steel safety lock slides into a groove on the pin for a secure and solid lock. Safety lock is mounted in a track system on the clevis body to help prevent it from being lost.

INCLUDES: Two 4-40 Safety Lock Kwik-Link Clevis'

REQUIRES: 4-40 Pushrods of modeler's choice Installing clevis' onto pushrods

SPECS: Length: 1-1/8" Width: 5/16" Shank Width: 3/16"

COMMENTS: For other sizes of safety lock clevis', use: 2-56 (DUBQ1510 qty 2) (DUBQ1511 qty 12) 4-40 (DUBQ1514 qty 2) (DUBQ1515 qty 12) 2mm (DUBQ1518 qty 2) (DUBQ1519 qty 12) 01 ir/jl

BOX DIMENSIONS: 3.00" W. X .50" H. X 3.00" L. BOX WEIGHT: .03 LBS.

1 / 1