

4505AT Cement-Carded 5/8 oz



tesr1525.jpg



4505AT Cement-Carded 5/8 oz

Rating: Not Rated Yet  
**Price**

Price with discount \$1.64

Salesprice with discount

Sales price \$1.64

Sales price without tax \$1.64

Discount

Tax amount

[Ask a question about this product](#)

#### Description

This is the 5/8 ounce (18ml) Carded Tube of Testors Cement For Metal and Wood.

**FEATURES:** Strong fast drying cement is specially formulated for joining wood, metal, polystyrene and most rigid plastic.

**INCLUDES:** One 5/8 ounce (18ml) Tube of Cement for Metal and Wood Models.

**REQUIRES:** Applying to both surfaces to be joined, allow to dry for a few seconds, press together, hold and allow two to four hours drying time for bonding metal, and twelve hours for bonding wood.

**COMMENTS:** CAUTION, Contains Toluol and Isopropyl Acetate. MAY CAUSE EYE, SKIN, NOSE AND THROAT IRRITATION. Keep away from heat, sparks and flame. Vapors may cause flash fire. Use only with adequate ventilation. Avoid breathing vapors and contact with eyes and skin. In case of eye contact, flush immediately with plenty of water and get medical attention. Recommended for modelers ages eight and older. Contains the deterrent Oil of Mustard (allyl isothiocyanate). For emergency health information, call 800-962-1253. Conforms to ASTM D-4236. WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. ir/jl

**BOX DIMENSIONS:** 2.50" W. X .75" H. X 7.00" L. **BOX WEIGHT:** .07 LBS.